

DIN 2558

Bridas ovaladas planas roscadas
Presion nominal 6.

Oval plain threaded flanges
Rated pressure 6.

Ovale Gremindeflansche, glatt
Nenndruck 6

Diámetro Nominal Rated Diameter Nennweite	Brida / Flange / Flansch								Tornillos / Screws / Schrauben		Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm3)
	d1	Rosca / Thread / Whitworth- Rohrgewinde DIN 2999	A	B	b	k	R	r	Rosca / Thread / Gewinde	d2	Kg
6	10,2	R 1/8	64	32	12	40	16	10	M 10	11	0,119
8	13,5	R 1/4	72	36	12	45	18	11	M 10	11	0,147
10	17,2	R 3/8	75	40	12	50	20	12	M 10	11	0,165
15	21,3	R 1/2	80	45	12	55	22,5	13	M 10	11	0,194
20	26,9	R 3/4	90	64	14	65	32	18	M 10	11	0,373
25	33,7	R 1	100	72	14	75	36	20	M 10	11	0,455
32	42,4	R 1 1/4	118	85	16	95	42,5	22	M 12	14	0,675
40	48,3	R 1 1/2	132	95	16	100	47,5	25	M 12	14	0,85
50	60,3	R 2	140	100	16	110	50	28	M 12	14	0,882
65	76,1	R 2 1/2	160	118	16	130	59	32	M 12	14	1,1
80	88,9	R 3	190	140	18	150	70	38	M 16	18	1,76
100	114,3	R 4	210	160	18	170	80	42	M 16	18	1,89

