

DIN 2629

Medidas en milímetros
Dimensions in mm
Maße in mm

Welding neck flanges
Rated pressure 320

Bridas con cuello para soldar
Presión nominal 320

Vorschweißflansche
Nenndruck 320

Tubo / Pipe / Rohr - AnschlußMaße			Brida / Flange / Flansch				Cuello / Neck / Ansatz				Resalto / Raised face / Dichtleiste		Tornillos / Screws / Schrauben			Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg /dm3)
Diámetro Nominal Rated Diameter Nennweite	d1		D	b	k	h1	d3	s	r	h2	d4	f	Numero / Number / Anzahl	Rosca / Thread / Gewinde	d2	
	ISO Serie 1 Reihe 1	DIN Serie 2 Reihe 2														
10	-	14	125	24	85	58	44	2,6	4	6	40	2	4	M 16	18	2,08
	17,2	-														
15	-	20	130	26	90	60	48	3,2	4	6	45	2	4	M 16	18	2,47
	21,3	-														
25	-	30	160	34	115	78	68	5	4	8	68	2	4	M20	22	5
	33,7	-														
40	-	44,5	195	38	145	88	92	6,3	6	10	88	3	4	M 24	26	8.25
	48,3	-														
50	63,5	-	210	42	160	100	106	8	6	10	102	3	8	M24	26	10,3
65	88,9	-	255	51	200	120	138	11	6	12	122	3	8	M27	30	19,1
80	101,6	-	275	55	220	130	156	12,5	8	14	138	3	8	M27	30	24,8
100	-	133	335	65	265	145	186	16	8	16	162	3	8	M 33	36	42
125	-	159	380	75	310	175	230	20	8	20	188	3	12	M33	36	64,5
	168,3	-														
150	193,7	-	425	84	350	195	265	25	10	25	218	3	12	M36	39	89,5
(175)	219,1	-	485	95	400	215	308	28	10	28	260	3	12	M 39	42	134
200	244,5	-	525	103	440	235	345	30	10	30	285	3	16	M 39	42	170
250	323,9	-	640	125	540	300	428	40	12	40	345	3	16	M48	52	308

