

DIN 2632

Bridas con cuello para soldar
Presion nominal 10

Welding neck flanges
Rated pressure 10

Vorschweißflansche
Nenndruck 10

Med das en milímetros
Dimensions in mm
Maße in mm

Tubo / Pipe / Rohr - AnschluBmabe			Brida / Flange / Flansch				Cuello / Neck / Ansatz				Resalto / Raised face / Dichtleiste		Tornillos / Screws / Schrauben			Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg /dm3)
Diámetro Nominal Rated Diameter Nennweite	d1		D	b	k	h1	d3	s	r	h2	d4	f	Numero / Number / Anzahl	Rosca / Thread / Gewinde	d2	Kg
	ISO Serie 1 Reihe 1	DIN Serie 2 Reihe 2														
10 a 150	Vease DIN 2633. Pres on nominal 16.															
10 to 150	See DIN 2633. Rated pressure 16.															
10 bis 150	VorschweiBflansche nach DIN 2633, Nenndruck 16 verwenden.															
200	219,1	-	340	24	295	62	235	5,9	10	16	268	3	8	M20	22	11,3
250	-	267	395	26	350	68	285	6,3	12	16	320	3	12	M20	22	14,7
	273	-					292									
300	323,9	-	445	26	400	68	344	7,1	12	16	370	4	12	M20	22	17,4
350	355,6	-	505	26	460	68	385	7,1	12	16	430	4	16	M20	22	23,6
	-	368														21,6
400	406,4	-	565	26	515	72	440	7,1	12	16	482	4	16	M24	26	28,6
	-	419														26,2
(450)	457	-	615	28	565	72	488	7,1	12	16	532	4	20	M24	26	31,5
500	508	-	670	28	620	75	542	7,1	12	16	585	4	20	M24	26	38,1
600	610	-	780	28	725	80	642	7,1	12	18	685	5	20	M27	30	44,6
700	711	-	895	30	840	80	745	8	12	18	800	5	24	M27	30	62,4
800	813	-	1015	32	950	90	850	8	12	18	905	5	24	M30	33	84,1
900	914	-	1115	34	1050	95	950	10	12	20	1005	5	28	M30	33	98,5
1000	1016	-	1230	34	1160	95	1052	10	16	20	1110	5	28	M33	36	115
1200	1220	-	1455	38	1380	115	1255	11	16	25	1330	5	32	M36	39	182
1400	1420	-	1675	42	1590	120	1460	12	16	25	1535	5	36	M39	42	248
1600	1620	-	1915	46	1820	130	1665	14	16	25	1760	5	40	M45	48	347
1800	1820	-	2115	50	2020	140	1868	15	16	30	1960	5	44	M45	48	430
2000	2020	-	2325	54	2230	150	2072	16	16	30	2170	5	48	M45	48	539
2200	2220	-	2550	58	2440	160	2275	18	18	35	2370	6	52	M 52	56	658
2400	2420	-	2760	62	2650	170	2478	20	18	35	2570	6	56	M 52	56	825
2600	2620	-	2960	66	2850	180	2680	22	18	40	2780	6	60	M 52	56	979
2800	2820	-	3180	70	3070	190	2882	22	18	40	3000	6	64	M 52	56	1156
3000	3020	-	3405	75	3290	200	3085	24	18	45	3210	6	68	M 56	62	1402